



The following technical datasheet is provided by Adesiv.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.
All information is correct at the time of download from the manufacturer.

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** info@wfa.uk.net • **W** www.wfa.uk.net

Registered in England under Company No: 03746590 VAT No: 765 9995 45



PAVILAST K32/S

CONSOLIDATING, DUST-REPELLENT ADHESION PROMOTER

Water-dispersed primer with silanised resin base, suitable for absorbent surfaces or **non-absorbent floors** (ceramic, natural stone, wooden floors, vinyl glue residues), before applying concrete-based skim-coats or self-levellers. PAVILAST K32/S can also be used on concrete screeds as a dust-repellent before bonding with our bicomponent or silane adhesives.

TECHNICAL CHARACTERISTICS:

- Monocomponent
- Water-based
- Easy to apply
- Suitable as a primer for bicomponent or silane adhesives

WHERE IT CAN BE APPLIED:

- Traditional concrete screeds
- Anhydrite screeds (calcium sulphate)
- Properly sanded wood or ceramic floors

DO NOT USE:

- On surfaces subject to continual rising damp that are not protected by a vapour seal barrier.

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Light blue liquid
Viscosity, Ford 4 at 20 °C (seconds):	11 - 13
Dry (%):	34 - 37
Yield: (g/m ²):	100 - 200
Working life (minutes):	5 - 20
Usage temperature (°C):	+15 - +25
Time before use (days):	1 - 3
Application/Equipment:	Roller, brush
Equipment cleaning:	Water, before the product sets
Storage (months): maximum temperature +5 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force
Packaging:	10 kg containers
Recommendations for use:	Do not apply in damp environments Frost sensitive Always use suitable personal protective equipment Always consult the technical and safety information sheets Allow the product to reach 20 °C before applying

SURFACE PREPARATION:

Always use suitable tools to check the moisture content in the sub-floor. The sub-floor must be compact, free from moisture and with loose parts, such as chalk, dust, oil or wax residue cleaned off.

APPLICATION:

Allow the product to reach 20 °C before use. Apply evenly to the sub-floor with a roller or brush. Avoid piling on too much product when applying. Before bonding with our bicomponent or silane adhesives, always check the moisture content of the screed as, due to its water-based formula, PAVILAST K32/S can increase the level of moisture. Optimum conditions for application are: Ambient temperature between 15 °C to 25 °C, relative humidity no greater than 75%. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

NOTES:

PAVILAST K32/S can also be used as an adhesion promoter for applications with PAVILAST R (on absorbent surfaces) or ADECEM FIBER (on absorbent and non-absorbent surfaces).

HAZARD PICTOGRAMS:

-- -- --



Adesiv s.r.l.

Revision nr. 1-EN

Dated 27/02/2020

PAVILAST K32/S

Printed on 27/02/2020

Page n. 1/10

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: K32/S
Product name: PAVILAST K32/S

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use: Aqueous dispersion based on modified acrylic resins.

For professional use.

1.3. Details of the supplier of the safety data sheet.

Name: Adesiv s.r.l.
Full address: Via Delle Rose, 31
District and Country: 36061 Bassano del Grappa (Vicenza)
Italia
Tel. +39 0424 566406
Fax. +39 0424 566473

e-mail address of the competent person.
responsible for the Safety Data Sheet. laboratorio@adesiv.it

1.4. Emergency telephone number.

For urgent inquiries refer to: Poison centres (24/24 h)
Italy: +39 02 6610 1029
Germany: +49 30 192 40
UK: +44 844 892 0111
France: +33 (0) 1 40 05 48 48
Spain: +34 91 562 0420
Russia: +7 495 628

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.
Hazard classification and indication:

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:



Adesiv s.r.l.

Revision nr. 1-EN

Dated 27/02/2020

PAVILAST K32/S

Printed on 27/02/2020

Page n. 2/10

EUH210
EUH208

Safety data sheet available on request.

Contains: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1); 1,2-benzisothiazol-3(2H)-one; 2-methyl-4-isothiazolin-3-one.

May produce an allergic reaction.

Precautionary statements:

--

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification.	Concentration, %	Classification 1272/2008 (CLP).	SCLs
2-methyl-4-isothiazolin-3-one CAS. 2682-20-4 EC. 220-239-6 INDEX. -	< 0,01	Acute Tox. 1 H330, Acute Tox. 3 H301, Skin Corr. 1A H314, Skin Sens. 1B H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411	Non applicabile.
1,2-benzisothiazol-3(2H)-one CAS. 2634-33-5 EC. 220-120-9 INDEX. 613-088-00-6	>= 0,005; < 0,05	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1	Skin Sens. 1; H317: C ≥ 0,05 %
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1) CAS. 55965-84-9 EC. - INDEX. 613-167-00-5	>=0,00015; < 0,0015	Acute Tox. 1 H330, Acute Tox. 2 H310, Acute Tox. 3 H301, Skin Corr. 1B H314, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1	Skin Irrit. 2; H315: 0,06 % ≤ C < 0,6 % Skin Sens. 1; H317: C ≥ 0,0015 % Eye Irrit. 2; H319: 0,06 % ≤ C < 0,6 % Skin Corr. 1B; H314: C ≥ 0,6 %

SECTION 4. First aid measures.



Adesiv s.r.l.

Revision nr. 1-EN

Dated 27/02/2020

PAVILAST K32/S

Printed on 27/02/2020

Page n. 3/10

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.
For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.



Adesiv s.r.l.

Revision nr. 1-EN

Dated 27/02/2020

PAVILAST K32/S

Printed on 27/02/2020

Page n. 4/10

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear



open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	light blue
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	> 100 °C.
Boiling range.	Not available.
Flash point.	> Not applicable.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	Not available.
Solubility	Miscible in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	10 – 13 seconds (ford cup #4), 20°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

VOC (ready-to-use product, Dir. 2004/42/CE, A-h/ba): 15 g/l

Solid residue: 35 – 37 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

**PAVILAST K32/S****10.4. Conditions to avoid.**

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.**11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:> 20 mg/l
LC50 (Inhalation - mists / powders) of the mixture:Not classified (no significant component).
LD50 (Oral) of the mixture:>2000 mg/kg
LD50 (Dermal) of the mixture:Not classified (no significant component).

1,2-Benzisotiazol-3(2H)-one
LD50 (Oral).1193 mg/kg rat
LD50 (Dermal).4115 mg/kg rat

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.**12.1. Toxicity.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.



Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)
LC50 - for Fish.

0,19 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea.

0,16 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants.

0,027 mg/l/72h Pseudokirchneriella subcapitata

Chronic NOEC for Fish.

0,05 mg/l Oncorhynchus mykiss, flusso, 14d

Chronic NOEC for Crustacea.

0,1 mg/l Daphnia magna, 21d

1,2-Benzisothiazolin-3(2H)-one

LC50 - for Fish.

2,18 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea.

2,94 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants.

0,11 mg/l/72h Pseudokirchneriella subcapitata

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.



Adesiv s.r.l.

Revision nr. 1-EN

Dated 27/02/2020

PAVILAST K32/S

Printed on 27/02/2020

Page n. 8/10

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:



None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 1	Acute toxicity, category 1
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H330	Fatal if inhaled.
H310	Fatal in contact with skin.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number



Adesiv s.r.l.

Revision nr. 1-EN

Dated 27/02/2020

PAVILAST K32/S

Printed on 27/02/2020

Page n. 10/10

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.