



The following technical datasheet is provided by Hermes.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.
All information is correct at the time of download from the manufacturer.

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** info@wfa.uk.net • **W** www.wfa.uk.net

Registered in England under Company No: 03746590 VAT No: 765 9995 45

VC 152 SK

Stable aluminium oxide abrasive paper for universal use

Product Benefits

- Sharp Aluminum oxide grain and open coating mean high stock removal rates
- Low loading characteristics
- Materials have very good surface quality
- Flexible paper backing
- Good price/performance ratio


Applications

- Used for manual and mechanical sanding on metal, wood, lacquer, paint, primer, filler, plastic and Aluminum.
- Boat-building, lacquer-processing furniture and wood industry, painters, cabinet-makers and carpenters, plastic processing industry, distributors

Product Structure

Type	15205
Grain	Aluminium oxide
Bonding	Resin
Backing	D-/C-weight paper, self-stick
Coating	open
Grit range	P 40, P 60 - P 240

Forms of Delivery



Strips



Discs



Metal



Wood



Lacquer



Composite

●● Very suitable

● Suitable

More information

www.hermes-abrasives.com

