



The following technical datasheet is provided by Loba.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.  
All information is correct at the time of download from the manufacturer.

---

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** [info@wfa.uk.net](mailto:info@wfa.uk.net) • **W** [www.wfa.uk.net](http://www.wfa.uk.net)

Registered in England under Company No: 03746590 VAT No: 765 9995 45

# TECHNICAL INFORMATION

## MarkantColor VARIOUS COLORS



### Even degree of gloss and full appearance

Colored natural hardwaxoil. High-quality, layer-building oils accentuate the natural look of the wood and at the same time achieve excellent resistance to dirt and water.

- Film-forming, wear-resistant
- Smooth and full bodied appearance
- Water and dirt resistant
- Easy and safe application
- Accentuates the natural beauty of the wood
- All variants can be mixed with each other
- Suitable for children's toys as per EN 71-3

### Range of use:


For staining of parquet and hardwood floors. Suitable for virtually all types of European and exotic timber. Note the LOBA wood types list, which can be found at [www.loba.de](http://www.loba.de). If in doubt, consult the factory.



## Technical Data

### Art.-no.

10508



All colors are also available in sample cans.

Solids	58.4 ±2%
Contents	aliphatic hydrocarbons, modified vegetable oils, pigments, vegetable waxes, siccatives
Storage and transportation	36 months of storage stability. No hazardous material according to ADR. Not sensitive to frost.
GISCODE	Ö60
2004/42/CE	EU limit value for this product (cat. A/i): 500 g/l (2010). This product contains max. 476 g/l VOC.



# TECHNICAL INFORMATION

# MarkantColor VARIOUS COLORS



## Technical Data

Basic colors							
	900005 Black	900126 White	900148 Grey				
Wood colors							
	800099 Mahogany	800127 Walnut	800132 Smoked oak	800145 Kambala	800149 Sucupira	800150 Wenge	800200 Antique oak
Trend colors							
	700133 Papyrus	900127 Chalk	900143 Oyster	900144 Clay	900145 Sand	900146 Pearl	900147 Silver

Color samples are not binding

11/12/2019



# TECHNICAL INFORMATION

# MarkantColor

## VARIOUS COLORS



## Application

- The surface must be sanded properly, wood moisture content max. 12%.
- The floor must be dry and free from any old coatings, oil, grease, wax, silicone, sanding dust and other contaminants. Room temperature +15°C to +25°C, relative humidity 40% to 65%, material temperature +18°C to +25°C. Ensure working areas are adequately ventilated.
- Transfer material to a LOBATool varnish bucket before applying.
- Shake the contents well.
- The innate color of the wood used, its structure and its pore properties, as well as the fineness of the sanding pattern, also have a major impact on the color that can be achieved. We strongly recommend to produce a color sample on the original wood using site-appropriate sanding techniques to check the result by yourself and if necessary for approval by the project client.
- Note the LOBA "Sanding instructions for coloring parquet flooring".
- Before using the color variants, we recommend carrying out a test application to assess the color tone that can be achieved and the overall visual effect. The colors can be mixed with each other. For lightening, or to reduce the coverage, the transparent variant can be added in. For an even color coverage, pigment saturation is required; dilution should therefore be carried out at most with three parts of transparent and one part color variant.
- If more than one container is being used for large areas, the total quantity must be mixed before work commences in a large container.
- On flooded surfaces, the deep penetration of the pigments into the wood means that it is not possible to restore the surface to its original condition.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at [www.wingis-online.de](http://www.wingis-online.de).
- This product is part of the LOBA and Wakol "Connected Systems". The approved combinations with Wakol parquet adhesives may be found in the "Connected Systems" Matrix: [www.loba.de/connected-systems](http://www.loba.de/connected-systems)

## Thinner

To lighten the shade or to reduce the coverage, mix with Markant semigloss. Max. 3 parts transparent to one part color.

## Application tool/application rate

Trowel application: LOBATool trowel / approx. 20 ml/m<sup>2</sup> (50m<sup>2</sup>/l)

roller and brush application: LOBATool oil roller Microfaser 60-80 or LOBATool oilbrush / approx. 60-100ml/m<sup>2</sup> (12m<sup>2</sup>/l)

## Drying time

- Earliest possible overcoating after 12 hours.
- However within 24 hours.
- Can be walked on after 12 hours.
- Usable after 24 hours.
- Coverage after 10 days.
- The floor can be covered earlier by using LOBATool Cover 400, for details see the TI for the product.

11/12/2019



# TECHNICAL INFORMATION

# MarkantColor

## VARIOUS COLORS



## Application

---

### Applying MarkantColor:

For coloring especially, we recommend following our sanding recommendations "Sanding instructions: coloring parquet flooring"

- Carefully apply MarkantColor in sections using a LOBATool trowel. On old floors with joints or bevelled wood planks, use the LOBATool oil roller Microfaser 60-80 as the wiper (do not roll).
- Immediately equalise with a single-disc machine and the LOBASAND SpecialPad beige underneath.
- Dry overnight, maximum 24 hours.
- Roll on a thin and even layer of Markant transparent using the LOBATool oil roller Microfaser 60-80. For light MarkantColor colors, MarkantNature can be applied as an alternative to the transparent version.

### Important information

In the case of interim drying periods of more than 24 hours, an interim sanding must be carried out before the application of a second layer. This is not possible with MarkantColor, hence the maximum interim drying periods must be unfailingly complied with. Otherwise adhesion problems will occur.

Keep soaked cloths, pads and other tools in closed containers. Moisten oil in combination with sanding dust, fabric cloths and so on with water or store in a sealable bucket and dispose of in a fire-safe manner, since otherwise there is a risk of self-ignition.

Trowel applications are only possible with joint-sealed wooden flooring. Oil that penetrates joints will not dry completely over a long period.

11/12/2019





# TECHNICAL INFORMATION

# MarkantColor VARIOUS COLORS



## General guidelines

---

**Cleaning of tools:** Clean tools with solvents such as brush cleaner.

**Drying time:** The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

**Side bonding:** Parquet that has not been shear-resistantly bonded in place, wood planks, wooden pavings, industrial parquet and parquet on underfloor heating as well as types of wood with a short moisture changing times (e.g. beech) show dimensional changes caused by quickly varying climate (rel. air humidity, temperature). When applying oil side bonding and thus unregular cracks in joints can not appear.

**Interactions:** Materials such as carpet underlays, furniture legs, castors, flexible adhesives used for parquet or for fixing can lead to softening and discoloration. Material building up in the joints can adversely affect touch and appearance. Exposure to hair dyes or rubber tyres on cars, motorcycles and cycles can lead to permanent, irreversible discoloration of the surface.

**Safety notes:** Flammable solvent vapours emerge during the drying process when working with products containing high quantities of solvents. As a result, fire, naked light, welding, smoking and so on are prohibited in the immediate vicinity of such products. Ventilate working areas and storage rooms well. Electrical equipment in workrooms and ancillary rooms must be switched off in sufficient time to ensure that they are cold when work begins. Any spark generation, including on electrical equipment, must be avoided. Keep material containers tightly closed. Solvent sensitive components, plants or animals (fish tanks) must be removed from areas at risk of exposure to solvent vapours.

**Connected Systems:** Connected Systems approved products are optimized in such way that no dark discoloration, caused by chemical interaction between surfacetreatment and adhesive occurs, when applied in accordance with the technical datasheets.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

11/12/2019



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.01.2020

Version number 16

Revision: 09.01.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name **LOBASOL Markant halbmatt/MarkantColor**

Article number: 10508-000

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture **Coating material**

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

LOBA GmbH & Co. KG  
Leonberger Straße 56 - 62  
D-71254 Ditzingen

Tel.: +49 (0)7156/357-0

##### Informing department:

Productmanagement  
e-mail: [service@loba.de](mailto:service@loba.de)

1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 **Void**

Hazard pictograms **Void**

Signal word **Void**

Hazard statements **Void**

Precautionary statements

P273 Avoid release to the environment.

Additional information:

EUH208 Contains Fatty acid C 18 unsaturated, reaction product with N,N-Dimethyl-1,3-propanediamine, 2-butanone oxime, cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Chemical characterisation: Mixtures

Description: Mixture of the substances listed below with harmless additions.

##### Dangerous components:

EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ☠ Asp. Tox. 1, H304	25-50%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy ☠ Flam. Liq. 3, H226; ☠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	≥10-<20%
CAS: 64742-47-8 EINECS: 265-149-8 Reg.nr.: 01-2119484819-18-XXXX	destillates (petroleum), hydrogenated light ☠ Asp. Tox. 1, H304	5-10%

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.01.2020

Version number 16

Revision: 09.01.2020

**Product name** LOBASOL Markant halbmatt/MarkantColor

(Contd. of page 1)

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** No special measures required.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**  
CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or water bodies.  
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class** 10
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 3)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.01.2020

Version number 16

Revision: 09.01.2020

**Product name** LOBASOL Markant halbmatt/MarkantColor

(Contd. of page 2)

### **SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**  
The usual precautionary measures should be adhered to in handling the chemicals.
- **Breathing equipment:** Not required.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
Nitrile rubber, NBR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  
Recommended thickness of the material:  $\geq 0.04$  mm
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.  
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).  
Value for the permeation: Level  $\leq 6$
- **Eye protection:** Safety glasses recommended during refilling.

### **SECTION 9: Physical and chemical properties**

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Brown
<b>Smell:</b>	Recognisable
<b>Odour threshold:</b>	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

<b>Melting point/freezing point:</b>	Not determined
<b>Initial boiling point and boiling range:</b>	130 °C
- **Flash point:** 65 °C
- **Inflammability (solid, gaseous)** Not applicable.
- **Decomposition temperature:** Not determined.
- **Self-inflammability:** Product is not selfigniting.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.01.2020

Version number 16

Revision: 09.01.2020

**Product name** *LOBASOL Markant halbmatt/MarkantColor*

(Contd. of page 3)

· <b>Explosive properties:</b>	Product is not explosive.
· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.
· <b>Steam pressure:</b>	Not determined.
· <b>Density at 20 °C</b>	0.904 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
dynamic at 20 °C:	260 mPas
kinematic:	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.01.2020

Version number 16

Revision: 09.01.2020

**Product name** *LOBASOL Markant halbmatt/MarkantColor*

(Contd. of page 4)

- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 1 (Self-assessment): slightly hazardous for water.*  
*Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Other adverse effects** *No further relevant information available.*

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
*After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.*

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

**SECTION 14: Transport information**

- |   |                 |
|---|-----------------|
| · <b>14.1 UN-Number</b><br>· <b>ADR, ADN, IMDG, IATA</b>                                    | Void            |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR, ADN, IMDG, IATA</b>                      | Void            |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, ADN, IMDG, IATA</b><br>· <b>Class</b> | Void            |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                     | Void            |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>                          | No              |
| · <b>14.6 Special precautions for user</b>  | Not applicable. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>            | Not applicable. |
| · <b>UN "Model Regulation":</b>   | Void            |

GB

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.01.2020

Version number 16

Revision: 09.01.2020

**Product name** *LOBASOL Markant halbmatt/MarkantColor*

(Contd. of page 5)

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

*These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

*Alteration in the context will be marked with a cross (\*).*

- **Relevant phrases**  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.
- **Department issuing data specification sheet:** Productmanagement.
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1
- **\* Data compared to the previous version altered.**

GB