



The following technical datasheet is provided by Wakol.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.
All information is correct at the time of download from the manufacturer.

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** info@wfa.uk.net • **W** www.wfa.uk.net

Registered in England under Company No: 03746590 VAT No: 765 9995 45

WAKOL Z 520 Thin Screed, fibre-reinforced

Technical Information

Area of application

Fibre-reinforced, very low-tension, self-levelling, cement-based thin screed, for offsetting unevenness in layer thicknesses between 3 - 40 mm

- Textile flooring
- Resilient flooring
- Parquet (minimum thickness of 3 mm)

for internal use format.

Special properties



1)



2)



3)



4)



5)



6)

- suitable for chair castors from a layer thickness of 3 mm
- very low tension
- can be pumped
- chromate reduced according to REACH
- self-levelling

- 1) Based on the criteria of GEV (Association for Emission-controlled Laying Materials), classified as EMICODE EC1 PLUS: very low in emissions
- 2) Emissions class according to French law
- 3) Cement-based products, low chromate
- 4) Meets the requirements of the European Community
- 5) Suitable for underfloor heating
- 6) Suitable for exposure to castor wheels

Technical data

Raw material base:	Mineral binding agent, synthetic resins
Mixture:	3,5 - 3,75 l water + 22 kg WAKOL Z 520 Thin Screed, fibre-reinforced
Working time:	approx. 30 minutes
Suitable for walking:	approx. 2 hours,
Waiting time before laying:	3 - 5 mm minimum 6 hours, > 5 mm up to 40 mm minimum 48 hours for all flooring and parquet

Storage time: 12 months; store in a cool and dry
location
EN 13818:2002: CT-C30-F8

Application and consumption⁷⁾:

Trowel or rakel approx 1,8 kg/m²/mm

7) Consumption is dependent on surface structure and absorbability of subfloor

Subfloors

The subfloor as well as the room climate conditions must meet the requirements of the applicable standards and data sheets. Subfloors must be permanently dry, solid, free from cracks, dirt and adhesion-inhibiting substances. Use a suitable mechanical procedure to remove separating layers.

Prime cement paving, calcium sulphate concrete, concrete and other absorbent subfloors with WAKOL D 3040 Primer Concentrate, diluted 1:2 with water, or with WAKOL D 3035 Dispersion Primer. Always comply with primer drying times.

When applying WAKOL Z 520 Thin Screed, fibre-reinforced to wooden floors like plywood a maximum levelling thickness of 6 mm is possible. Use WAKOL D 3045 Special Primer on wooden floors exclusively.

New, well sanded, standardized cast asphalt concrete does not require a primer when applying to a maximum depth of 10 mm. Prime worn and poorly sanded cast asphalt concrete with WAKOL D 3040 Primer Concentrate, diluted 1:1 with water, or with WAKOL D 3035 Dispersion Primer.

Usage

Stir WAKOL Z 520 Thin Screed, fibre-reinforced in a clean mixing vessel with 3,5 - 3,75 litres of clear, cold tap water until free of lumps. The mixing device must not exceed 600 rpm. Using a pin knife, dripper, or smoothing trowel, uniformly apply the mixed compound to the subfloor in the desired layer thickness (at least 3 mm). We recommend using a spiked roller. Before applying the levelling compound, check whether a sufficiently sized edge strip is available.

Protect the levelling compound layer from direct sunlight and draughts while it sets.

Important

Processing not below floor temperature of +15 °C and room temperature of +18 °C, as well as room humidity preferably between 40 % and 65 %, maximum 75 %. All information is based on approx. 20° C and 50 % relative air humidity. Acclimatize all laying materials before installation in these conditions.

When applying the levelling compound in a layer thickness over 5 mm on calcium sulphate-bonded screeds, use only Wakol reaction primer such as WAKOL PU 280 Polyurethane Primer. Please consult the corresponding data sheet.

The permissible layer thickness over timber substrates is 6 mm, over mastic asphalt (IC10 and IC15) the max. is 10 mm.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardized conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com. This Technical Information of 01.03.2021 supersedes all previous versions.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** WAKOL Z 520 Thin-screed, fibre-reinforced
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Knife filler/ Surfacers
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
WAKOL GmbH
Bottenbacher Str. 30
D-66954 Pirmasens
info@wakol.com
+49 6331 8001 0
- **Informing department:**
Product safety department.
msds@wakol.de
- **1.4 Emergency telephone number:**
Emergency CONTACT (24-Hour-Number):
GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



corrosion

Eye Dam. 1 H318 Causes serious eye damage.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Cement, portland, chemicals
- **Hazard statements**
H318 Causes serious eye damage.
- **Precautionary statements**
P261 Avoid breathing dust.
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

Trade name: WAKOL Z 520 Thin-screed, fibre-reinforced

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.



SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Knifing filler / Surfacers

· **Dangerous components:**

CAS: 65997-15-1 Cement, portland, chemicals ≥3-≤5%

EINECS: 266-043-4  Eye Dam. 1, H318;  Skin Irrit. 2, H315

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation** Supply fresh air; consult doctor in case of complaints.

· **After skin contact** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Avoid formation of dust.

Ensure adequate ventilation

· **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

· **6.3 Methods and material for containment and cleaning up:** Pick up mechanically.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

Trade name: WAKOL Z 520 Thin-screed, fibre-reinforced

See Section 13 for disposal information.

(Contd. of page 2)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in dry conditions.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**
65997-15-1 Cement, portland, chemicals
WEL Long-term value: $10 * 4 ** \text{ mg/m}^3$
*inhalable dust **respirable dust
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Recommended filter device for short term use:** Filter P2
- **Hand protection**



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

- **Material of gloves**
Nitrile rubber, NBR
Recommended thickness of the material: $\geq 0.35 \text{ mm}$
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

Trade name: WAKOL Z 520 Thin-screed, fibre-reinforced

(Contd. of page 3)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

· **Body protection: Protective work clothing**

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Colour:	According to product specification
· Smell:	Odourless
· Odour threshold:	Not determined.
· Melting point/freezing point:	>1,250 °C
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not determined.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable.
· Self-inflammability:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH at 20 °C	>11 (ISO 976)
· Viscosity:	
· Kinematic viscosity	Not applicable.
· kinematic (calculated) at 40°C:	
· dynamic:	Not applicable.
· Solubility	
· Water:	Soluble.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Steam pressure:	Not applicable.
· Density and/or relative density	
· Density at 20 °C	3 g/cm ³ (EN ISO 2811-1)
· Relative density	Not determined.
· Settled apparent density	900–1,300 kg/m ³
· Vapour density	Not applicable.

· **9.2 Other information**

· **Appearance:**

· **Form:** Powder

· **Important information on protection of health and environment, and on safety.**

· **Explosive properties:** Product does not present an explosion hazard.

· **VOC** 0.00 %

· **Solids content:** 100.00 % (DIN EN 827.8.2)

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

Trade name: WAKOL Z 520 Thin-screed, fibre-reinforced

(Contd. of page 4)

- **Change in condition**
- **Evaporation rate** Not applicable.
- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:**
- 7778-18-9 calcium sulphate, natural**
- Oral LD50 >5,000 mg/kg (rat)
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
- Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

Trade name: WAKOL Z 520 Thin-screed, fibre-reinforced

(Contd. of page 5)

- **11.2 Information on other hazards**
 - **Endocrine disrupting properties**
- None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
 - **12.2 Persistence and degradability** No further relevant information available.
 - **12.3 Bioaccumulative potential** No further relevant information available.
 - **12.4 Mobility in soil** No further relevant information available.
 - **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
 - **12.6 Endocrine disrupting properties**
 - The product does not contain substances with endocrine disrupting properties.
 - **12.7 Other adverse effects**
 - **Additional ecological information:**
 - **General notes:**
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, ADN, IMDG, IATA** Void
- **14.2 UN proper shipping name**
- **ADR, ADN, IMDG, IATA** Void
- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG, IATA**
- **Class** Void
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:** Not applicable.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.02.2021

Version number 1

Revision: 23.02.2021

Trade name: WAKOL Z 520 Thin-screed, fibre-reinforced

(Contd. of page 6)

- **14.6 Special precautions for user** Not applicable.
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
- **Transport/Additional information:** Not dangerous according to the above specifications.
- **UN "Model Regulation":** Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **GEV-Guideline/EMICODE:** EC 1, "very low emission"
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H315 Causes skin irritation.

H318 Causes serious eye damage.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1