

Product Data Sheet

Genuine Reclaimed Oak Plank Unfinished Rustic



Should you require the information on any other details please contact the sales team on **020 8501 6730** or **info@wfa.uk.net**

MADE IN BRITAIN



Product Details

Product Description:	Genuine Reclaimed Oak
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Plank
Grade:	Rustic
Total Thickness:	20.5mm
Width/s:	215 - 225mm
Length/s:	Random 600 - 2400mm
Wear Layer:	5.5mm Oak Wear Layer
Core Layer:	15mm Multi Layer Birch Plywood
Profile:	Tongue & Grooved and Ends Matched
Edge Profile:	2 Sided Micro Bevelled
Finish:	Heavy Brushed - Unfinished

Technical Information

Country of Manufacture:	Europe
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 13227
Reaction to Fire:	EN 13501-1 Dfl-S2
Density:	710 - 735 kg/m ³
Formaldehyde Emissions:	Class E1 Zero Emissions
Warmth Conduction (approx):	0.130 - 0.140 W/m K
Production Tolerances;	
Width:	+/- 0.20mm
Thickness (Total):	+/- 0.20mm
Length:	+/- 0.20mm
90° Angle:	+/- 0.05°
Guarantee:	25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

Grading

Maximum Size of Sound Knots:	Unlimited
Maximum Size of Filled Knots:	Filled to maximum 60 – 70 mm Larger knots are cut off
Filled Defects:	Allowed
Filled Type:	Black Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Character Variation:	Original Bandsawn and Planer Marks with Irregular Edges Allowed
Grain Variation:	Mixture of Natural Grain, Open Splits, Holes, Knots, and Dead Worm Holes

Installation

Installation Method:	Glued	Nailed	Floated on Underlay
<i>Please also refer to our guidelines.</i>	✓	✓	✓
Over Underfloor Heating:	Yes - Suitable for use with water and electric systems. Maximum surface temperature 27°C. Floor probes required to regulate the sub floor surface temperature. Fidbox recommended to record the surface temperature & relative humidity above and below the floor.		
Site Conditions:	45 – 65% relative humidity and 15 – 25°C room temperature.		

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
Oiled Finish				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓



Irregular edges



Bandsawn



Partially filled cracks



Partially filled knots



Woodworm* and sapwood

pds-genuine-reclaimed-oak-plank-unfinished-rustic

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. Installation and Warranty: The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

*Please note that ALL woodworm is no longer alive.

Wood Floors & Accessories Limited

Spilsby Road • Harold Hill • Romford • RM3 8SB

T 020 8501 6730 • E info@wfa.uk.net • W www.wfa.uk.net