Product Data Sheet

Solid Blocks Oak Rustic 22mm





Should you require the information on any other details please contact the sales team on **020 8501 6730** or **info@wfa.uk.net**









Product Details

Product Description:	T&G Wood Blocks				
Wood Species:	European Oak				
Construction:	Solid				
Product Type:	Blocks				
Grade:	Rustic				
Total Thickness:	22mm				
Width:	70mm				
Length/s:	230 / 280 / 350mm				
Wear Layer:	N/A				
Core Layer:	N/A				
Profile:	Tongue & Grooved All Round				
Edge Profile:	Square Edged				
Finish:	Unfinished				

Technical Information

Country of Manufacture:	Europe				
FSC®:	FSC MIX Credit FSC-C111710				
Lamination:	N/A				
Glue Line:	N/A				
Norm:	EN 14342:2005+A1:2008				
Reaction to Fire:	C _{fl} -S1				
Density:	650 kg/m3				
Formaldehyde Emissions:	Class E1 Zero Emissions				
Warmth Conduction (approx):	22mm – 0.16 W/m K				
Production Tolerances;					
Width:	+/- 0.2mm				
Thickness (Step Between Pieces):	+/- 0.2mm Unfinished +/- 0.5mm Finished				
Length:	+/- 0.5mm				
90° Angle:	+/- 0.2°				

Grading

Maximum Size of Sound Knots:	Up to 70mm
Maximum Size of Filled Knots:	Up to 35mm
Filled Defects:	Not Filled
Sap Wood:	Minimal Edge and Core Sap Wood
Cracks:	Possible
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

Installation

installation						
Installation Method:	Glued	Nailed	Floated on Underlay			
Please also refer to our guidelines.	1					
NOTE: The fully bonded method of installation is recommended.						
Over Underfloor Heating: N/A						

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
Oiled Finish				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
Lacquered Finish				
Bona Cleaner:		✓		
Bona Refresher:				✓

Guarantee: 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.