

Product Data Sheet

End Grain Oak Cobbles Premium



Should you require the information on any other details please contact the sales team on **+44 (0) 20 8501 6730** or **info@wfa.uk.net**



MAGNITUDE
Sustainable Magnetic Wood Flooring



Product Details

Product Description:	End Grain Cobbles
Wood Species:	European Oak
Construction:	Solid
Product Type:	End Grain
Grade:	Premium
Total Thickness:	18mm*
Width:	40mm*
Length:	85mm*
Profile:	Square Edged Planed All Round
Finish:	Unfinished Tumbled

Technical Information

Country of Manufacture:	Europe
FSC®/PEFC:	On Request
Norm:	DIN 68702
Reaction to Fire:	EN 13501-1 Dfl-S2
Density:	675 - 770 kg/m3
Formaldehyde Emissions:	N/A
Warmth Conduction (approx):	Max 30mm – < 0,15m2/K/W
Production Tolerances;	
Width:	+/- 1.00mm
Thickness (Total):	+/- 1.00mm
Length:	+/- 1.00mm
90° Angle:	+/- 0.05°

- Produced in Europe • Look for our FSC®-certified products

*Sizes are subject to availability and can differ from the above dimensions.

Grading

Maximum Size of Sound Knots:	No Maximum
Open Knots:	Not Allowed
Cracks:	Open Cracks up to 1mm Allowed
Sap Wood:	Not Allowed
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

Installation

Installation Method: Glued Nailed Floated on Underlay

Please also refer to our guidelines. ✓

Over Underfloor Heating: When glued to an appropriate subfloor this product is suitable for use with water systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or www.floorprotector.at (Minimal shrinkage can occur)

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
Oiled Finish				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
Lacquered Finish				
Bona Cleaner:		✓		
Bona Refresher:				✓

Guarantee: 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

29/10/24 Replaces 25/04/2024

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. **Installation and Warranty:** The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer with the skills and knowledge to take into account individual site circumstances. This is in accordance with and comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

Wood Floors & Accessories Limited

Spilsby Road • Harold Hill • Romford • RM3 8SB • United Kingdom

T +44 (0) 20 8501 6730 • E info@wfa.uk.net • W www.wfa.uk.net