

# Product Data Sheet

## Parquet Strip Oak Prime - Also known as overlays



Should you require the information on any other details please contact the sales team on **020 8501 6730** or [info@wfa.uk.net](mailto:info@wfa.uk.net)

**MADE IN BRITAIN**



### Product Details

|                      |   |
|----------------------|---|
| Product Description: | 10mm Parquet Strip  |
| Wood Species:        | European Oak  |
| Construction:        | Solid   |
| Product Type:        | Strip   |
| Grade:               | Prime   |
| Total Thickness:     | 10mm  |
| Width/s:             | 100 / 150 / 180mm   |
| Length/s:            | 100mm Random 600 - 2500mm<br>( Average 1400mm )<br>150 / 180mm Random 1400 - 2500mm<br>( Average 1800mm ) |
| Wear Layer:          | N/A   |
| Core Layer:          | N/A   |
| Profile:             | Square Edged  |
| Edge Profile:        | Square Edged  |
| Finish:              | Unfinished  |

### Technical Information

|                             |                       |
|-----------------------------|-----------------------|
| Country of Manufacture:     | Europe                |
| FSC®:                       | FSC 100% FSC-C111710  |
| Lamination:                 | N/A                   |
| Glue Line:                  | N/A                   |
| Norm:                       | EN 14342:2013         |
| Reaction to Fire:           | Cl-s1                 |
| Density:                    | 630 kg/m <sup>3</sup> |
| Formaldehyde Emissions:     | N/A                   |
| Warmth Conduction (approx): | 10mm – 0.074 W/m K    |
| Production Tolerances;      |                       |
| Width:                      | +/- 0.09mm            |
| Thickness (Total):          | +/- 0.20mm            |
| Length:                     | +/- 0.09mm            |
| 90° Angle:                  | +/- 0.05°             |

### Grading

|                               |   |
|-------------------------------|---|
| Maximum Size of Sound Knots:  | Not Allowed - Occasional Pin Knots < 10mm |
| Maximum Size of Filled Knots: | Not Allowed                               |
| Filled Defects:               | Not Allowed                               |
| Sap Wood:                     | Minimal Edge and Core Sap Wood            |
| Colour Variation:             | Natural Variation Allowed                 |
| Grain Variation:              | Mixture of Natural Grain                  |

### Installation

Installation Method:                      Glued    Pinned    Floated on Underlay

*Please also refer to our guidelines.*                      ✓                      ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

| Recommended Products    | Initial | Regular | Monthly | Long Term |
|-------------------------|---------|---------|---------|-----------|
| Sweep / Vacuum:         | ✓       | ✓       |         |           |
| <b>Oiled Finish</b>     |         |         |         |           |
| Osmo Wash and Care:     |         | ✓       |         |           |
| Osmo Maintenance Oil:   |         |         |         | ✓         |
| <b>Lacquered Finish</b> |         |         |         |           |
| Bona Cleaner:           |         | ✓       |         |           |
| Bona Refresher:         |         |         |         | ✓         |

**Guarantee:** 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.