

Product Data Sheet

Parquet Strip Oak Quarter Sawn - Also known as overlays



Should you require the information on any other details please contact the sales team on **+44 (0) 20 8501 6730** or **info@wfa.uk.net**



MAGNITUDE
Sustainable Magnetic Wood Flooring



Product Details

| | |
|----------------------|--|
| Product Description: | 9mm Parquet Strip |
| Wood Species: | French Oak |
| Construction: | Solid |
| Product Type: | Strip |
| Grade: | Quarter Sawn |
| Total Thickness: | 9mm |
| Width/s: | 100 / 140 / 180mm |
| Length/s: | Random 1000 - 2500mm (Average 1800mm) |
| Wear Layer: | N/A |
| Core Layer: | N/A |
| Profile: | Square Edged |
| Edge Profile: | Square Edged |
| Finish: | Unfinished |

Technical Information

| | |
|-----------------------------|-----------------------|
| Country of Manufacture: | Europe |
| Lamination: | N/A |
| Glue Line: | N/A |
| Standard: | BS 13227 |
| Reaction to Fire: | BS 13501-1 Dfl-S2 |
| Density: | 710 kg/m ³ |
| Formaldehyde Emissions: | N/A |
| Warmth Conduction (approx): | 9mm – 0.148 W/m K |
| Production Tolerances; | |
| Width: | +/- 0.20mm |
| Thickness (Total): | +/- 0.20mm |
| Length: | +/- 0.20mm |
| 90° Angle: | +/- 0.1 ° |

Grading

| | |
|-------------------------------|---|
| Maximum Size of Sound Knots: | Not Allowed - Occasional Pin Knots < 10mm |
| Maximum Size of Filled Knots: | Not Allowed |
| Filled Defects: | Not Allowed |
| Sap Wood: | Minimal Edge and Core Sap Wood |
| Colour Variation: | Natural Variation Allowed |
| Grain Variation: | Straight Grain and Medullary Rays |

Installation

Installation Method: Glued Pinned Floated on Underlay

Please also refer to our guidelines. ✓ ✓

NOTE: The fully bonded method of installation is recommended.

Over Underfloor Heating: When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or www.floorprotector.at

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

| Recommended Products | Initial | Regular | Monthly | Long Term |
|-------------------------|---------|---------|---------|-----------|
| Sweep / Vacuum: | ✓ | ✓ | | |
| Oiled Finish | | | | |
| Osmo Wash and Care: | | ✓ | | |
| Osmo Maintenance Oil: | | | | ✓ |
| Lacquered Finish | | | | |
| Bona Cleaner: | | ✓ | | |
| Bona Refresher: | | | | ✓ |

Guarantee: 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

30/10/24 Replaces 25/04/2023

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. **Installation and Warranty:** The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer with the skills and knowledge to take into account individual site circumstances. This is in accordance with and comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

Wood Floors & Accessories Limited

Spilsby Road • Harold Hill • Romford • RM3 8SB • United Kingdom

T +44 (0) 20 8501 6730 • E info@wfa.uk.net • W www.wfa.uk.net