

# Product Data Sheet

## Parquet Strip Oak Rustic Monastery - Also known as overlays



Should you require the information on any other details please contact the sales team on **+44 (0) 20 8501 6730** or **info@wfa.uk.net**



**MAGNITUDE**  
Sustainable Magnetic Wood Flooring



### Product Details

Product Description:	9mm Parquet Strip
Wood Species:	French Oak
Construction:	Solid
Product Type:	Strip
Grade:	Rustic Monastery
Total Thickness:	9mm
Width:	210mm
Length/s:	Random 1000 - 2500mm ( Average 1800mm )
Wear Layer:	N/A
Core Layer:	N/A
Profile:	Square Edged
Edge Profile:	Square Edged
Finish:	Unfinished

### Technical Information

Country of Manufacture:	Europe
Lamination:	N/A
Glue Line:	N/A
Standard:	BS 13227
Reaction to Fire:	BS 13501-1 Dfl-S2
Density:	710 kg/m <sup>3</sup>
Formaldehyde Emissions:	N/A
Warmth Conduction (approx):	9mm – 0.148 W/m K
Production Tolerances;	
Width:	+/- 0.20mm
Thickness (Total):	+/- 0.20mm
Length:	+/- 0.20mm
90° Angle:	+/- 0.1 °

### Grading

Maximum Size of Sound Knots:	Up to 70mm
Maximum Size of Filled Knots:	Up to 35mm
Filled Defects:	Allowed
Filled Type:	Coloured Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Cracks:	Possible
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

### Installation

Installation Method:                      Glued    Pinned    Floated on Underlay

*Please also refer to our guidelines.*                      ✓                      ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

**Site Conditions:** 45 – 65% relative humidity & 15 – 25°C room temperature.

### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
<b>Oiled Finish</b>				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
<b>Lacquered Finish</b>				
Bona Cleaner:		✓		
Bona Refresher:				✓

**Guarantee:** 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

30/10/24 Replaces 25/04/2023

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. **Installation and Warranty:** The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer with the skills and knowledge to take into account individual site circumstances. This is in accordance with and comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

**Wood Floors & Accessories Limited**

Spilsby Road • Harold Hill • Romford • RM3 8SB • United Kingdom

T +44 (0) 20 8501 6730 • E [info@wfa.uk.net](mailto:info@wfa.uk.net) • W [www.wfa.uk.net](http://www.wfa.uk.net)