

Product Data Sheet

Stability 12 Engineered Chevron Character



Should you require the information on any other details please contact the sales team on **020 8501 6730** or **info@wfa.uk.net**

MADE IN BRITAIN



Product Details

Product Description:	Stability 12
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Chevron 45° ^
Grade:	Character
Total Thickness:	12mm
Width:	120mm
Length:	600mm
Wear Layer:	3mm Oak Wear Layer
Core Layer:	9mm Multi Layer Birch Plywood
Profile:	Tongue & Grooved Left & Right Ends
Edge Profile:	1.50mm 4 Sided Micro Bevel or Square Edged
Finish:	Unfinished, Filled and Sanded / UV Cured Oiled - Matt, Silk or Satin / BF

Technical Information

Country of Manufacture:	Europe
FSC®:	FSC® 100% certified
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 14342:2013
Reaction to Fire:	Di-s1
Density:	650 kg/m ³
Formaldehyde Emissions:	Class E1 Zero Emissions
Warmth Conduction (approx):	12mm – 0.088 W/m K
Production Tolerances;	
Width:	+/- 0.2mm
Thickness (Above T&G):	+/- 0.2mm
Length:	+/- 0.2mm
90° Angle:	+/- 0.3°
Guarantee:	25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

Grading

Maximum Size of Sound Knots:	Up to 70mm
Maximum Size of Filled Knots:	Up to 35mm
Filled Defects:	Allowed
Filled Type:	Coloured Filler
Sap Wood:	≤ 20% of the surface area of the board
Cracks:	Possible
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

Installation

Installation Method:	Glued	Nailed	Floted on Underlay
<i>Please also refer to our guidelines.</i>	✓		
Over Underfloor Heating:	Yes - Suitable for use with water and electric systems. Maximum surface temperature 27°C. Floor probes required to regulate the sub floor surface temperature. Fidbox recommended to record the surface temperature & relative humidity above and below the floor.		
Site Conditions:	45 – 65% relative humidity and 15 – 25°C room temperature.		

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
Oiled Finish				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
Lacquered Finish				
Bona Cleaner:		✓		
Bona Refresher:				✓

^ Alternative angles and sizes are available on request.

pds-stab-12-chevron-character

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. Installation and Warranty: The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

Wood Floors & Accessories Limited

Spilsby Road • Harold Hill • Romford • RM3 8SB

T 020 8501 6730 • E info@wfa.uk.net • W www.wfa.uk.net