

Product Data Sheet

Stability 20 Engineered Chevron Rustic



Should you require the information on any other details please contact the sales team on **+44 (0) 20 8501 6730** or **info@wfa.uk.net**



MAGNITUDE
Sustainable Magnetic Wood Flooring



Product Details

Product Description:	Stability 20
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Chevron 45° ^
Grade:	Rustic
Total Thickness:	20mm
Profile:	Tongue & Grooved with Left & Right Ends
Edge Profile:	Square Edged or 1.50mm 4 Sided Micro Bevel
Finish:	Unfinished, Filled and Sanded / UV Cured Oiled - Matt, Silk or Satin / BF
Size/s:	500 x 90mm / 600 x 120mm
Wear Layer:	6mm Oak Wear Layer
Core Layer:	14mm Multi Layer Birch Plywood

Technical Information

Country of Manufacture:	Europe
FSC®:	FSC 100% FSC-C111710
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 14342:2013
Reaction to Fire:	Cl-s1
Density:	650 kg/m ³
Formaldehyde Emissions:	Class E1 Zero Emissions
VOC Content:	Zero to low Emissions
Warmth Conduction (approx):	20mm – 0.148 W/m K
Production Tolerances;	
Width:	+/- 0.2mm
Thickness (Above T&G):	+/- 0.2mm
Length:	+/- 0.2mm
90° Angle:	+/- 0.3°

^ Alternative angles and sizes are available on request.

Grading

Maximum Size of Sound Knots:	Up to 70mm
Maximum Size of Filled Knots:	Up to 35mm
Filled Defects:	Allowed
Filled Type:	Coloured Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Cracks:	Possible
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

Installation

Installation Method: Glued Nailed Floated on Magnitude Underlay Flooring

Please also refer to our guidelines. ✓ ✓ ▼

NOTE: The fully bonded method of installation is recommended.

Over Underfloor Heating: When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or www.floorprotector.at

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
Oiled Finish				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
Lacquered Finish				
Bona Cleaner:		✓		
Bona Refresher:				✓

Guarantee: 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

▼ Magnitude Flooring powered by WFA & IOBAC is suitable for installation over metal raised access flooring only, see installation guidelines.

01/11/24 Replaces 30/04/2023

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. **Installation and Warranty:** The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer with the skills and knowledge to take into account individual site circumstances. This is in accordance with and comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

Wood Floors & Accessories Limited

Spilsby Road · Harold Hill · Romford · RM3 8SB · United Kingdom

T +44 (0) 20 8501 6730 · E info@wfa.uk.net · W www.wfa.uk.net