


# Product Data Sheet

## Stability 15 / 20mm Design Cube - Prime / Rustic



Should you require the information on any other details please contact the sales team on **020 8501 6730** or [info@wfa.uk.net](mailto:info@wfa.uk.net)

**MADE IN BRITAIN**



### Product Details

Product Description:	Stability 15 / 20mm
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Cube
Grade:	Prime / Rustic
Total Thickness:	15 / 20mm
Size:	200mm Wide
Wear Layer:	4 / 6mm Oak Wear Layer
Core Layer:	11 / 14mm Multi Layer Birch Plywood
Profile:	Partly T&G, Partly False Tongues
Edge Profile:	1.50mm 4 Sided Micro Bevel
Finish:	UV Cured Oiled - Matt, Silk or Satin / Unfinished, Filled and Sanded / BF

### Technical Information

Country of Manufacture:	Europe
FSC®:	FSC 100% FSC-C111710
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 14342:2005+A1:2008
Reaction to Fire:	15mm - Dfl-s1 / 20mm - Cfl-s1
Density:	650 kg/m <sup>3</sup>
Formaldehyde Emissions:	Class E1 Zero Emissions
Warmth Conduction (approx):	Up to 0.16 W/m K
Production Tolerances;	
Width:	+/- 0.25mm
Thickness (Total):	+/- 0.10mm
Length:	+/- 0.25mm
90° Angle:	+/- 0.3°

**Guarantee:** 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

### Grading

#### PRIME

Maximum Size of Sound Knots:	Not Allowed - Occasional Pin Knots < 10mm
Maximum Size of Filled Knots:	Not Allowed
Filled Defects:	Not Allowed
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain

#### RUSTIC

Maximum Size of Sound Knots:	Up to 60mm
Maximum Size of Filled Knots:	Up to 25mm
Filled Defects:	Allowed
Filled Type:	Coloured Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

### Installation

Installation Method: Glued Nailed Floated on Underlay

*Please also refer to our guidelines.* ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.


### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
<b>Oiled Finish</b>				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
<b>Lacquered Finish</b>				
Bona Cleaner:		✓		
Bona Refresher:				✓

# Product Data Sheet

## Stability 15 / 20mm Design Cube Fumed - Prime / Rustic



Should you require the information on any other details please contact the sales team on **020 8501 6730** or **info@wfa.uk.net**

**MADE IN BRITAIN**



### Product Details

Product Description:	Stability 15 / 20mm
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Cube
Grade:	Prime / Rustic
Treatment:	Fumed *
Total Thickness:	15 / 20mm
Size:	200mm Wide
Wear Layer:	4 / 6mm Oak Wear Layer
Core Layer:	11 / 14mm Multi Layer Birch Plywood
Profile:	Partly T&G, Partly False Tongues
Edge Profile:	1.50mm 4 Sided Micro Bevel
Finish:	UV Cured Oiled - Matt, Silk or Satin / Unfinished, Filled and Sanded / BF

### Technical Information

Country of Manufacture:	Europe
FSC®:	FSC 100% FSC-C111710
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 14342:2005+A1:2008
Reaction to Fire:	15mm - Dfl-s1 / 20mm - Cf-s1
Density:	650 kg/m <sup>3</sup>
Formaldehyde Emissions:	Class E1 Zero Emissions
Warmth Conduction (approx):	Up to 0.16 W/m K
Production Tolerances;	
Width:	+/- 0.25mm
Thickness (Total):	+/- 0.10mm
Length:	+/- 0.25mm
90° Angle:	+/- 0.3°

**Guarantee:** 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

### Grading

#### PRIME

Maximum Size of Sound Knots:	Not Allowed - Occasional Pin Knots < 10mm
Maximum Size of Filled Knots:	Not Allowed
Filled Defects:	Not Allowed
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain

#### RUSTIC

Maximum Size of Sound Knots:	Up to 60mm
Maximum Size of Filled Knots:	Up to 25mm
Filled Defects:	Allowed
Filled Type:	Coloured Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

### Installation

Installation Method: Glued Nailed Floated on Underlay

*Please also refer to our guidelines.* ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
<b>Oiled Finish</b>				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
<b>Lacquered Finish</b>				
Bona Cleaner:		✓		
Bona Refresher:				✓

# Product Data Sheet

## Stability Design Cube - Prime / Rustic



Available in the following Bespoke Core Range Colours - for alternative options please contact us.



BF497 \*



BF512



BF638\*



BF808



BF902



BF903



BF904



BF911



BF920 \*



BF922 \*



BF929 \*



BF939



BF941 \*



BF1976 \*



BF2811 \*



BF2830



BF3630



BF3767



BF3796

\* Our fumed and smoked colours are achieved through a process which reacts with the natural tannins in the oak. Although we use controlled processes when smoking **variation in colour will occur** and the final colours are dictated by nature and not by using pigmented stains.

# Product Data Sheet

## Stability Design Cube - Prime / Rustic



Dimensions - small tolerances allowed

