

Product Data Sheet

Stability 15 Engineered Herringbone Rustic



Should you require the information on any other details please contact the sales team on **+44 (0) 20 8501 6730** or **info@wfa.uk.net**



MAGNITUDE
Sustainable Magnetic Wood Flooring



Product Details

| | |
|----------------------|---|
| Product Description: | Stability 15 |
| Wood Species: | European Oak |
| Construction: | Engineered |
| Product Type: | Herringbone |
| Grade: | Rustic |
| Total Thickness: | 15mm |
| Profile: | Tongue & Grooved with Left & Right Ends |
| Finish: | Unfinished, Filled and Sanded / UV Cured Oiled - Matt or Satin / BF |

| | |
|---------------|---------------------------------|
| Size/s: | 350 x 70mm * |
| Edge Profile: | Square Edged |
| Wear Layer: | 4mm Oak Wear Layer |
| Core Layer: | 11 mm Multi Layer Birch Plywood |

| | |
|---------------|---------------------------------|
| Size/s: | 500 x 90mm / 600 x 120mm |
| Edge Profile: | 1.50mm 4 Sided Micro Bevel |
| Wear Layer: | 4mm Oak Wear Layer |
| Core Layer: | 11 mm Multi Layer Birch Plywood |

Technical Information

| | |
|-----------------------------|-------------------------|
| Country of Manufacture: | Europe |
| FSC®: | FSC 100% FSC-C111710 |
| Lamination: | Hydraulic Cold Press |
| Glue Line: | D3 Water Based Glue |
| Norm: | EN 14342:2013 |
| Reaction to Fire: | Dfl-s1 |
| Density: | 650 kg/m ³ |
| Formaldehyde Emissions: | Class E1 Zero Emissions |
| VOC Content: | Zero to low Emissions |
| Warmth Conduction (approx): | 15mm – 0.111 W/m K |
| Production Tolerances; | |
| Width: | +/- 0.2mm |
| Thickness (Above T&G): | +/- 0.2mm |
| Length: | +/- 0.2mm |
| 90° Angle: | +/- 0.3° |

NOTE: Sizes shown in red are non stock items, delivery will be 7 - 10 weeks, subject to finish.

* Square edged, NOT FSC, available in BF tumbled finishes only.

Grading

| | |
|-------------------------------|------------------------------------|
| Maximum Size of Sound Knots: | Up to 40mm |
| Maximum Size of Filled Knots: | Up to 15mm |
| Filled Defects: | Allowed |
| Filled Type: | Coloured Filler |
| Sap Wood: | Minimal Edge and Core Sap Wood |
| Cracks: | Possible |
| Colour Variation: | Natural Variation Allowed |
| Grain Variation: | Mixture of Natural Grain and Knots |

Installation

Installation Method: Glued Nailed Underlay Floating on Magnitude Flooring

Please also refer to our guidelines. ✓

NOTE: The fully bonded method of installation is recommended.

Over Underfloor Heating: When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fibox which measures and logs the temperature and humidity levels, see the data sheet for more information or www.floorprotector.at

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

| Recommended Products | Initial | Regular | Monthly | Long Term |
|----------------------|---------|---------|---------|-----------|
| Sweep / Vacuum: | ✓ | ✓ | | |

Oiled Finish

| | | | | |
|-----------------------|--|---|--|---|
| Osmo Wash and Care: | | ✓ | | |
| Osmo Maintenance Oil: | | | | ✓ |

Lacquered Finish

| | | | | |
|-----------------|--|---|--|---|
| Bona Cleaner: | | ✓ | | |
| Bona Refresher: | | | | ✓ |

Guarantee: 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

▼ Magnitude Flooring powered by WFA & IOBAC is suitable for installation over metal raised access flooring only, see installation guidelines.

08/05/25 Replaces 06/11/24

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. **Installation and Warranty:** The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer with the skills and knowledge to take into account individual site circumstances. This is in accordance with and comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

Wood Floors & Accessories Limited

Spilsby Road · Harold Hill · Romford · RM3 8SB · United Kingdom

T +44 (0) 20 8501 6730 · E info@wfa.uk.net · W www.wfa.uk.net