

Product Data Sheet

Stability Design Panel 3 - Prime / Rustic



Should you require the information on any other details please contact the sales team on **020 8501 6730** or **info@wfa.uk.net**



Product Details

| | |
|----------------------|--|
| Product Description: | Stability 15mm |
| Wood Species: | European Oak |
| Construction: | Engineered |
| Product Type: | Design Panel 3 |
| Grade: | Prime / Rustic |
| Total Thickness: | 15mm |
| Size: | 660 x 660mm |
| Wear Layer: | 4mm Oak Wear Layer |
| Core Layer: | 11mm Multi Layer Birch Plywood |
| Profile: | Grooved to all Sides & Supplied with False Tongues |
| Edge Profile: | Square Edged |
| Finish: | Unfinished, Filled and Sanded <i>Some Finishing Available</i> <ul style="list-style-type: none"> • Bevelled • Distressed Edges • Brushed - Light, Medium or Heavy • BF Finishing Available in Hardwax Oil |

Technical Information

| | |
|-----------------------------|---|
| Country of Manufacture: | Europe |
| Lamination: | Hydraulic Cold Press |
| Glue Line: | D3 Water Based Glue |
| Norm: | EN 14342:2013 |
| Reaction to Fire: | Di-s1 |
| Density: | 650 kg/m ³ |
| Formaldehyde Emissions: | Class E1 Zero Emissions |
| Warmth Conduction (approx): | 0.16 W/m K |
| Production Tolerances; | |
| Width: | +/- 0.25mm |
| Thickness (Total): | +/- 0.10mm |
| Length: | +/- 0.25mm |
| 90° Angle: | +/- 0.3° |
| Guarantee: | 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details. |

Grading

PRIME

| | |
|-------------------------------|---|
| Maximum Size of Sound Knots: | Not Allowed - Occasional Pin Knots < 10mm |
| Maximum Size of Filled Knots: | Not Allowed |
| Filled Defects: | Not Allowed |
| Sap Wood: | Minimal Edge and Core Sap Wood |
| Colour Variation: | Natural Variation Allowed |
| Grain Variation: | Mixture of Natural Grain |

RUSTIC

| | |
|-------------------------------|------------------------------------|
| Maximum Size of Sound Knots: | Up to 60mm |
| Maximum Size of Filled Knots: | Up to 25mm |
| Filled Defects: | Allowed |
| Filled Type: | Dark Brown Filler |
| Sap Wood: | Minimal Edge and Core Sap Wood |
| Colour Variation: | Natural Variation Allowed |
| Grain Variation: | Mixture of Natural Grain and Knots |

Installation

| | |
|---|--|
| Installation Method: | Glued Nailed Floated on Underlay |
| <i>Please also refer to our guidelines.</i> | ✓ |
| Over Underfloor Heating: | Yes - Suitable for use with water and electric systems. Maximum surface temperature 27°C. Floor probes required to regulate the sub floor surface temperature. Fidbox recommended to record the surface temperature & relative humidity above and below the floor. |
| Site Conditions: | 45 – 65% relative humidity and 15 – 25°C room temperature. |

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

| Recommended Products | Initial | Regular | Monthly | Long Term |
|-------------------------|---------|---------|---------|-----------|
| Sweep / Vacuum: | ✓ | ✓ | | |
| Oiled Finish | | | | |
| Osmo Wash and Care: | | ✓ | | |
| Osmo Maintenance Oil: | | | | ✓ |
| Lacquered Finish | | | | |
| Bona Cleaner: | | ✓ | | |
| Bona Refresher: | | | | ✓ |